

Table of contents

Introduction	3
Nonionic surfactants	4-9
Bio-based nonionic surfactants	10-11
Polypropylene glycols and random copolymers	12
Anionic surfactants	13
Low foam surfactants	14-15





A broad range of nonionic and anionic products

Including...

DOWFAX[™] Anionic Surfactants ECOSURF[™] Nonionic Surfactants TERGITOL™ Nonionic Surfactants TRITON™ Anionic and Nonionic Surfactants

Dow surfactants include some of the most familiar anionic and nonionic products in the industry, known worldwide for excellent emulsification and dispersion. They increase the cleaning and wetting properties of household, industrial and institutional cleaning products. Dow surfactants are also used by formulators of paints, coatings and inks for pigment wetting, film leveling and pigment and dye stabilization.

Dow surfactants contribute desired mechanical properties and storage stability to emulsion polymerization systems, including styrene-butadiene, vinyl, acrylic and other copolymer latex resin systems. They are also broadly used in agricultural formulations, textile processing, paper manufacturing and oilfield operations.

An overview of Dow surfactants

This brochure provides an overview for Dow nonionic, anionic, and low foam surfactant products. Included are products which are:



Readily biodegradable

*Readily biodegradable as defined in OECD Guidelines for the Testing of Chemicals, Section 3 (Rev. 23 March 2006)



CleanGredients™

CleanGredients™ is a database of chemical ingredients used primarily to formulate residential, institutional, industrial and janitorial cleaning products that have been pre-approved to meet the U.S. EPA's Safer Choice Standard.



EPA inerts list

Dow produces surfactants that act as emulsifiers, dispersants, wetting agents for crop protection and antimicrobial products. These surfactants can be used as Inert Ingredients in pesticide and antimicrobial formulations under EPA Inert Regulations. See the EPA website for specific EPA Status https://iaspub.epa.gov/apex/pesticides/f?p=inertfinder:mixtures.



EU Ecolabel

EU Ecolabel is a label of environmental excellence that evaluates raw material extraction, production, distribution and disposal.



We invite you to review the product features, physical and performance properties and application information for more detail.

Total support capabilities

Our investments in surfactant products and technology create one of the strongest capability platforms in the industry while providing sustainable and safer product alternatives.

Dow is your collaborative source for solutions. We will work closely with you to find innovative, more sustainable answers to address all of your surfactant requirements.

For your convenience, we offer a comprehensive library of starting formulations and technical information at **www.dowsurfactants.com**. Information is frequently updated to meet the latest requirements for formulation performance and sustainability.

With Dow surfactants, you also receive...

- A wide range of chemistries
- Extensive applications expertise
- The knowledge and resources to innovate
- · Expertise and awareness of current regulations and legislation
- · A global sales, distribution and technical support network
- Global supply from world-class manufacturing facilities
- The strength and stability of Dow for confidence and peace of mind

Product	Product highlights	APE based ¹	Cloud point ²	HLB ³	Moles EO	CMC ⁴ / Surface tension ⁵	Foam height ⁶	Pour point ⁷	Form ⁸	Features	Applications
	ries Nonionic Sur	rfactants ar								surfactants that provide performance comparable to all le processing, and any application in which excellent we	
ECOSURF™ EH-3 Surfactant	948	No	Disp	7.9	PRT	480/30	0/0	-21	L	Excellent oil-soluble emulsifier, low foam, low odor, good handling, very low aquatic toxicity, listed on CleanGredients™ for US EPA Safer Choice Formulations	Cleaners and degreasers, textiles, agrochemicals
ECOSURF™ EH-6 Surfactant	9 4 8 £	No	40	10.8	PRT	914/30	20/0	5	L	Exceptional wetting and hard surface cleaning, low odor, excellent handling and formulation properties. very low aquatic toxicity, listed on CleanGredients™ for US EPA Safer Choice Formulations	Concentrates, cleaners and detergents, paints and coatings, textile processing, agrochemicals
ECOSURF™ EH-9 Surfactant	9 4 3 &	No	61	12.5	PRT	1066/31	60/0	16	L	Exceptional wetting and hard surface cleaning, low odor, excellent formulation properties, very low aquatic toxicity, Listed on CleanGredients™ for US EPA Safer Choice Formulations	Concentrates, cleaners and detergents, paints coatings, textile processing, agrochemicals
ECOSURF™ EH-9 (90%) Surfactant	9 4 8 2	No	61	12.5	PRT	1066/31	60/0	-5	L	Exceptional wetting and hard surface cleaning, low odor, improved handling and formulation properties, very low aquatic toxicity, listed on CleanGredients™ for US EPA Safer Choice Formulations	Concentrates, cleaners and detergents, prewash spotters, paints and coatings, textile processing, agrochemicals
ECOSURF™ EH-14 (90%) Surfactant	9 4 8 E	No	86	14	PRT	4018/32	70/10	6	L	Exceptional wetting and hard surface cleaning, low odor, improved handling and formulation properties, very low aquatic toxicity, listed on CleanGredients™ for US EPA Safer Choice Formulations	Concentrates, cleaners and detergents, prewash spotters, paints and coatings, textile processing, agrochemicals
ECOSURF™ EH-40 (75%) Surfactant	98	No	>100	18.0	PRT	8454/46	100/45	3	L	Excellent emulsion stabilizer, low odor, improved handling and very low aquatic toxicity	Emulsion polymerization, paints and coatings, agrochemicals, floor polish and wax emulsions







⁶Ross-Miles foam height: mm at 0.1 wt% actives, 25°C, initial / 5 minute

"Pour point: "C
"Form at 25°C: L = Liquid, S = Solid
MWF= Metalworking fluids
Ins = Insoluble

Disp = Dispersible PRT = Proprietary

⁵Surface tension: dynes/cm at 1% actives, 25°C





ECOSURF™ products are sold under trade name TERGITOL™ in Canada and Japan.

Footnotes:

¹APE = Alkyl phenol ethoxylate

²Cloud point: °C, 1 wt% actives aqueous solution

³HLB range: <10 w/o emulsifier, >10 o/w emulsifier, 10-15 good wetting, 12-15 detergents

4Critical micelle concentration: ppm at 25°C

Product	Product highlights	APE based¹	Cloud point ²	HLB ³	Moles EO	CMC⁴/ surface tension⁵	Foam height ⁶	Pour point ⁷	Form ⁸	Features	Applications
	Ionionic Surfacta	ants are vers	atile, high per							n unbeatable combination of performance and cost in a wide range of formulating applications.	when used in place of Primary Alcohol
TERGITOL™ 15-S-3 Surfactant	98	No	Insoluble	8.0	3	Ins	Ins	-46	L	Excellent hydrocarbon compatibility and detergency	Defoamers, textile, pulp/paper, prewash spot removers, agrochemicals, dry cleaners
TERGITOL™ 15-S-5 Surfactant	9 \$	No	Dispersible	10.5	5	Disp	Disp	-25	L	Excellent emulsifier and detergent, enhances paint associative thickener efficiency, aids in rinseability of solvent-based systems	Paints and coatings, cleaners, prewash spot removers, agrochemicals, dry cleaners, textile, oilfield
TERGITOL™ 15-S-7 Surfactant	9 \$	No	37	12.1	7	38/30	117/28	1	L	Excellent wetting and rinseability, excellent formulation and handling properties	Paints and coatings, cleaners, prewash spot removers, agrochemicals, textile, pulp/paper, oilfield
TERGITOL™ 15-S-9 Surfactant	9 6 3 Water	No	60	13.3	9	52/30	124/43	9	L	Excellent detergency, rapid dissolution and good rinseability, low odor, excellent formulation and handling properties, listed on CleanGredients™ for US EPA Safer Choice Formulations	High performance cleaners, paints and coatings, agrochemicals, textile, pulp/paper, oilfield
TERGITOL™ 15-S-12 Surfactant	263	No	89	14.5	12	104/33	124/43	22	S	Excellent detergent and dispersant, good handling properties, higher temperature wetting, listed on CleanGredients™ for US EPA Safer Choice Formulations	Agrochemicals, dispersions, high temperature systems
TERGITOL™ 15-S-12 (90%) Surfactant	963	No	89	14.5	12	107/34	130/28	-8	L	Excellent detergent and dispersant, good handling properties, higher temperature wetting, listed on CleanGredients™ for US EPA Safer Choice Formulations	Agrochemicals, dispersions, high temperature systems
TERGITOL™ 15-S-15 Surfactant	268	No	>100	15.4	15	162/36	126/24	29	S	High HLB emulsifier and dispersant, provides freeze thaw and ionic stability, listed on CleanGredients™ for US EPA Safer Choice Formulations	Emulsion polymerization, paper and textile processing, solid cleaners
TERGITOL™ 15-S-20 Surfactant	9 \$	No	>100	16.3	20	315/38	112/42	35	S	Excellent emulsion stabilizer with low reactor residue, provides freeze thaw and ionic stability, good handling properties	Emulsion polymerization, paper and textile processing, solid cleaners
TERGITOL™ 15-S-20 (80%) Surfactant	9 \$	No	>100	16.3	20	315/38	112/42	6	L	Excellent emulsion stabilizer with low reactor residue, provides freeze thaw and ionic stability, good handling properties	Emulsion polymerization, paints and coatings, floor polish and wax emulsions
TERGITOL™ 15-S-30 Surfactant	98	No	>100	17.4	31	558/43	115/30	39	S	Excellent emulsion stabilizer with low reactor residue, provides freeze thaw and ionic stability	Emulsion polymerization, paints and coatings, floor polish and wax emulsions
TERGITOL™ 15-S-40 Surfactant	9 \$	No	>100	18.0	41	783/44	110/24	43	S	Emulsion stabilizer, provides freeze thaw and ionic stability, good handling properties	Emulsion polymerization, paint and coatings, floor polish and wax emulsions
TERGITOL™ 15-S-40 (70%) Surfactant	98	No	>100	18.0	41	1314/45	103/28	5	L	Emulsion stabilizer, provides freeze thaw and ionic stability, good handling properties	Emulsion polymerization, paint and coatings, floor polish and wax emulsions



Product highlights	APE based ¹	Cloud point ²	HLB ³	Moles EO	CMC ⁴ / surface tension ⁵	Foam height ⁶	Pour point ⁷	Form ⁸	Features	Applications
ce, nonionic sur	factants fo	or defoamii	ng, wettii	ng and en		RGITOL™ S	Surfactants	deliver lo	w foam, excellent solvency, chemical stability and reliabl	e formulation performance in a number of
968	No	18	-	PRT	1886/35	Ins	-39	L	Foam control agent, wetting agent and dispersant	Foam control, food processing, paper processing and chemical intermediates.
96 S Corte	No	24	3	PRT	-/40	0/0	-32	L	Efficient foam control, wetting agent. AOF (Antioxidant free) version is listed on CleanGredients™ and approved for US EPA Safer Choice formulations	Foam control for fermentation, food washing, water treatment, MWF, machine dishwash, food and dairy process cleaning, agrochemicals
94 S Corate	No	32	7	PRT	-/41	45/30	-2	L	Efficient foam control agent, wetting agent	Foam control for fermentation, MWF, machine dishwash, food and dairy process cleaning, paints and coatings, agrochemicals
26 S Corder	No	62	15	PRT	-/44	48/18	7	L	Higher temperature foam control, good detergency	Fermentation, food processing, adhesives, paper processing, MWF, sanitizing solutions
968	No	20	2	PRT	-/36	Disp	-20	L	Low temperature foam control	Fermentation, MWF, chemical intermediates
\$	No	18	1	PRT	-/33	30/25	-24	L	Low temperature foam control	Fermentation processes, MWF
\$	No	80	13.0	PRT	-/33	96/71	32	S	Excellent detergent and emulsifier agent, effective steric stabilizer and wetting agent	Agrochemicals, iodophors and high temperature systems
\$	No	90	13.8	PRT	-/39	99/84	45	S	Excellent detergent and emulsifier agent, effective steric stabilizer and wetting agent	Agrochemicals, high temperature systems
98	No	31	-	PRT	12/38	40/12	-40	L	Foam control agent, wetting agent and dispersant	Foam control, MWF, household cleaning, water treatment, agrochemicals, chemical intermediates and paper processing
\$	No	35	-	PRT	29/45	30/0	-43	L	Foam control agent, wetting agent and dispersant	Foam control, MWF, household and industrial cleaning, paints and coatings, agrochemicals, chemical intermediates and paper processing
98	No	45	-	PRT	56/44	0/0	0	L	Foam control agent, wetting agent and dispersant	Foam control, MWF, household and industrial cleaning, paints and coatings, agrochemicals, chemical intermediates and paper processing
-	No	50	10	PRT	-	-	-29	L	Low foaming, high chemical and thermal stability, easily rinsed from surfaces	Fermentation processing, textile processing, paints and coatings, metal cleaners, agrochemicals
	highlights hylene Oxide/I ice, nonionic sure od processing, ice of the second	highlights based¹ hylene Oxide/Propylene hyle	highlights based¹ point² hylene Oxide/Propylene Oxide (Etc. pe, nonionic surfactants for defoaming and other processing, metalworking and other processing,	hylene Oxide/Propylene Oxide (EO/PO) Care, nonionic surfactants for defoaming, wetting and other applied processing, metalworking and other applied processing. No 18 - No 24 3 No 24 3 No 32 7 No 80 15 No 80 13.0 No 90 13.8 No 90 13.8 No 35 - No 35 -	highlights based¹ point² PLB³ EO hylene Oxide/Propylene Oxide (EO/PO) Copolyment be, nonionic surfactants for defoaming, wetting and enter applications. No 18 - PRT No 24 3 PRT No 32 7 PRT No 62 15 PRT No 18 1 PRT No 80 13.0 PRT No 90 13.8 PRT No 90 13.8 PRT No 35 - PRT No 45 No 45 - PRT	Product highlights APE based¹ Cloud point² HLB³ Moles EO surface tension⁵ Impleme Oxide/Propylene Oxide (EO/PO) Copolymers be, nonionic surfactants for defoaming, wetting and emulsifying. Tend processing, metalworking and other applications. Tended processing, metalworking and other applications. Image: PRT of the processing	APE based based	Product highlights based Product highlights based Product based Produ	Product No No 18 - PRT -/40 No No No No No No No N	Product highlights based based points HLBs Moles ECOPO Copolymers 29. nonlonic surfactants for defoaming, wetting and emulsifying. TERGITOL™ Surfactants deliver low foam, excellent solvency, chemical stability and reliable disprocessing, metalworking and other applications. 2



⁷Pour point: °C

⁸Form at 25°C: L = Liquid, S = Solid MWF= Metalworking fluids

Ins = Insoluble

Disp = Dispersible PRT = Proprietary

Footnotes:

¹APE = Alkyl phenol ethoxylate

²Cloud point: °C, 1 wt% actives aqueous solution


³HLB range: <10 w/o emulsifier, >10 o/w emulsifier, 10-15 good wetting, 12-15 detergents

⁴Critical micelle concentration: ppm at 25°C

⁵Surface tension: dynes/cm at 1% actives, 25°C

⁶Ross-Miles foam height: mm at 0.1 wt% actives, 25°C, initial / 5 minute

Product	Product highlights	APE based ¹	Cloud point ²	HLB ³	Moles EO	CMC ⁴ / surface tension ⁵	Foam height ⁶	Pour point ⁷	Form ⁸	Features	Applications
	tants are versatile	nonionic spe	ecialty surface	ctants that						ueous systems. They are used in conjunction with cillization of iodine for germicidal cleaners.	ther surfactants to provide stability
TERGITOL™ XD	S Coultel	No	74	-	PRT	-/38	60/25	34	s	Excellent steric and freeze thaw stabilizer, effective pigment and carbon black dispersant	Agrochemicals, paints and coatings dispersions iodophors, emulsion polymerization
TERGITOL™ XH	S Covabel	No	95	-	PRT	-/41	80/40	40	S	Provides lubricity, effective steric and freeze thaw stabilizer, solubilizes iodine	Fiber lubricants, emulsion polymerization, iodophors. agrochemicals
TERGITOL™ XJ	S Collect	No	49	-	PRT	-/36	53/13	27	S	Excellent emulsifier for aromatic and chlorinated solvents, steric and freeze thaw stabilizer	Emulsion and dispersion systems, emulsion polymerization, agrochemicals
TERGITOL™ TMN Br TERGITOL™ TMN Ser and paints and coating	ries surfactants a				agents havi	ng low aqueous	s dynamic an	d equilibriur	n surface pr	rofiles. They offer excellent performance in cleaners,	emulsification polymerization,
TERGITOL™ TMN-3	S College	No	Ins	8.1	3	Ins	Ins	-49	L	Excellent oil soluble emulsifier, hydrocarbon compatibility	Low HLB emulsifier for textiles and paper applications, degreasers
TERGITOL™ TMN-6 (90%)	S Cookel	No	36	13.1	8	800/27	130/22	<-40	L	Excellent wetting agent, penetrant and dispersant, silicone emulsifier, narrow gel range	Paper and textile processing, pigment and wax/resin dispersants, hard surface cleaners, agrochemicals, paints and coatings
TERGITOL™ TMN-100X (90%)	\$ 644	No	65	14.0	9	830/27	150/24	-6	L	Non-APE alternative for TRITON™ X-100, excellent wetting, penetrant and dispersant, superior emulsification	Paints and coatings, paper & textile processing pigment and wax/resin dispersants, cleaners
TERGITOL™ TMN-10 (90%)	S Corabel	No	76	14.4	11	1313/30	118/28	-19	L	High temperature penetrant and dispersant, high HLB emulsifier, narrow gel range	Paper and textile processing, pigment and wax/resin dispersants, cleaners, paints and coatings
TRITON™ Specialty And These TRITON™ surface and oilfield chemicals.	actants are used a	as emulsifiers	, wetting age	ents or det	ergents in a	applications inc	luding paints	and coating	gs, agroche	micals, paper and textile processing, emulsification	systems, household and industrial cleaning
TRITON™ HW 1000	S Eviden	No	Ins	10.8	5	Ins	Ins	-18	L	Non-silicone-based, superior wetting and leveling agent, low foaming, wets various substrates, improves gloss and smoothness of coating films, penetrant and rapid pigment dispersant, narrow gel range	Inks and printing, waterborne and laminate adhesives, coatings, paints, paper & textile processing, pigment and wax/resin dispersion, agrochemicals









Footnotes:

¹APE = Alkyl phenol ethoxylate

²Cloud point: °C, 1 wt% actives aqueous solution

³HLB range: <10 w/o emulsifier, >10 o/w emulsifier, 10-15 good wetting, 12-15 detergents

⁴Critical micelle concentration: ppm at 25°C ⁵Surface tension: dynes/cm at 1% actives, 25°C

⁶Ross-Miles foam height: mm at 0.1 wt% actives, 25°C, initial / 5 minute

"Pour point: °C
"Form at 25°C: L = Liquid, S = Solid
MWF= Metalworking fluids
Ins = Insoluble
Disp = Dispersible
PRT = Proprietary

Product	Product highlights	APE based¹	Cloud point ²	HLB ³	Moles EO	CMC ⁴ / surface tension ⁵	Foam height ⁶	Pour point ⁷	Form ⁸	Features	Applications
TERGITOL™ NP Nor TERGITOL™ NP Serie cleaning applications	es Surfactants co	over a wide	range of e	thoxylatio	n and HLE	3 values. The	ey are used	as emulsif	iers, wettir	ng agents and dispersants in a variety of applic	ations, including emulsion polymerization,
TERGITOL™ NP-4	\$	Yes	Ins	8.9	4	Ins	Ins	-28	L	Excellent oil-soluble surfactant, low HLB emulsifier	Cleaners and degreasers, dry cleaning, dispersant for petroleum oil
TERGITOL™ NP-6	\$	Yes	Ins	10.9	6	Ins	Ins	-26	L	Excellent emulsifier, wetting agent, stabilizer, couples detergent range nonionics into hydrocarbon systems	Cleaners and degreasers, dry cleaning, adhesives, agrochemicals
TERGITOL™ NP-7	\$	Yes	20	12.0	7	39/32	20/19	-19	L	Excellent detergency, outstanding wetting	Cleaners and degreasers, paper and textile processing, prewash spotters, agrochemicals, MWF, oilfield chemicals
TERGITOL™ NP-8	\$	Yes	43	12.6	8	61/32	103/95	-6	L	Excellent detergency, outstanding wetting, good rinseability	Cleaners and detergents, paper and textile processing, paints and coatings, agrochemicals, MWF
TERGITOL™ NP-9	\$	Yes	54	12.9	9	60/32	105/90	-1	L	Excellent detergency, outstanding wetting, good rinseability	Cleaners and detergents, paper and textile processing, laundry, paints and coatings, dust control, agrochemicals, MWF
TERGITOL™ NP-9.5	\$	Yes	59	13.1	9.5	62/32	115/102	7	L	Excellent detergency, outstanding wetting	Cleaners and detergents, paper and textile processing, paints and coatings, agrochemicals, MWF
TERGITOL™ NP-10	\$	Yes	63	13.2	10	55/33	115/110	6	L	Excellent detergency, outstanding wetting	Cleaners and detergents, paper and textile processing, paints and coatings, agrochemicals, MWF
TERGITOL™ NP-11	\$	Yes	72	13.5	11	71/34	112/92	11	L	Excellent detergency, outstanding wetting	Cleaners and detergents, paper and textile processing, paints and coatings, agrochemicals, MWF
TERGITOL™ NP-12	\$	Yes	78	13.8	12	85/35	117/115	13	L	Excellent detergency, outstanding wetting	Cleaners and detergents, paper and textile processing, paints and coatings, agrochemicals, MWF
TERGITOL™ NP-13	\$	Yes	82	13.9	13	66/35	118/97	14	L	Excellent detergency, outstanding wetting	Cleaners and detergents, paper and textile processing, paints and coatings, agrochemicals, MWF
TERGITOL™ NP-15	-	Yes	>100	15.0	15	90/41	128/95	25	S	Excellent detergency, outstanding wetting, suitable for higher temperatures	Cleaners and detergents, paper and textile processing, paints and coatings, agrochemicals, MWF
TERGITOL™ NP-30	\$	Yes	>100	17.1	30	157/46	125/77	37	S	Highly water soluble emulsifier and stabilizer, effective at high temperatures	Wetting agents and stabilizers, emulsifiers and dispersants, agrochemicals
TERGITOL™ NP-30 (70%)	\$	Yes	>100	17.1	30	160/42	125/77	-8	L	Highly water soluble emulsifier and stabilizer, effective at high temperatures	Wetting agents and stabilizers, emulsifiers and dispersants, agrochemicals
TERGITOL™ NP-40	8	Yes	>100	17.8	40	230/50	123/115	48	S	Effective at high temperatures, highly water-soluble emulsifier and stabilizer, wetting	Paper and textile processing, paints and coatings, agrochemicals
TERGITOL™ NP-40 (70%)	\$	Yes	>100	17.8	40	232/50	123/115	2	L	Effective at high temperatures, highly water-soluble emulsifier and stabilizer	Paper and textile processing, paints and coatings, agrochemicals
TERGITOL™ NP-50 (70%)	\$	Yes	>100	18.2	50	256/53	115/110	2	S/L	Effective at high temperatures, highly water-soluble emulsifier and stabilizer	Paper and textile processing, paints and coatings, agrochemicals
TERGITOL™ NP-55 (70%)	-	Yes	>100	18.3	55	39/45	105/60	15	S/L	Effective at high temperatures, highly water-soluble emulsifier and stabilizer	Paper and textile processing, paints and coatings, agrochemicals
TERGITOL™ NP-70 (70%)	\$	Yes	>100	18.7	70	287/51	105/100	15	S	Effective at high temperatures, highly water-soluble emulsifier and stabilizer	Paper and textile processing, paints and coatings, agrochemicals



Nonionic sui	riactants										
Product	Product highlights	APE based ¹	Cloud point ²	HLB ³	Moles EO	CMC ⁴ / surface tension ⁵	Foam height ⁶	Pour point ⁷	Form ⁸	Features	Applications
TRITON™ RW Am TRITON™ RW Seri and deliver excepti	es Surfactants o	ffer unique re		factancy, a	llowing fo	r easier sepa	ration of en	nulsified oil	s from aqueou	us waste streams. They are especially well-suite	d for industrial laundry applications
TRITON™ RW-20	-	No	Ins	6-8	2	Ins	Ins	< -6	L	Oil soluble emulsifier, pH reversible	Degreasers, MWF
TRITON™ RW-50	-	No	Disp	12-14	5	260/29 pH=12 -/51 pH=2	28/2 pH=12	< -6	L	Low HLB emulsifier, pH reversible	Metal cleaners, industrial laundry, transportation cleaners, MWF
TRITON™ RW-150	-	No	>100	>16	15	860/30 pH=12 -/54 pH=2	135/15 pH=12	11	L	pH reversible properties and emulsification	High temperature systems
TRITON™ X Octyl TRITON X Series si of applications, inc	urfactants are ver luding emulsion	rsatile nonio						xylation and	I HLB values.	They are used as emulsifiers, wetting agents an	, , , , , , , , , , , , , , , , , , ,
TRITON™ X-15	9 3	Yes	Ins	4.9	1.5	Ins	Ins	3	L	Oil soluble emulsifier, solubilizer	Defoamers, dye solubilizer, chemical intermediate
TRITON™ X-35	98	Yes	Ins	7.8	3	Ins	Ins	-9	L	Excellent compatibility with aliphatic or aromatic hydrocarbons and polar organic solvents	Defoamers, pulp/paper, textile, dry cleaning, MWF, chemical intermediate
TRITON™ X-45	9 \$	Yes	Disp	9.8	4.5	136/29	23/9	-24	L	Excellent emulsifier with good wetting, aids in rinseability of solvent-based systems	Defoamers, cleaners, MWF, agrochemicals, paints and coatings, textile, pulp/paper, oilfield
TRITON™ X-114	98	Yes	25	12.3	7.5	120/31	55/40	-14	L	Excellent wetting and detergency	Cleaners, paints and coatings, pulp/paper, textile, agrochemicals, MWF, oilfield
TRITON™ X-100	9 \$	Yes	66	13.4	9.5	189/33	128/107	1	L	Excellent detergent, dispersant, and emulsifier for oil-in-water systems	Household and industrial cleaners, paints and coatings pulp/paper, textile, agrochemicals, MWF, oilfield
TRITON™ X-102	\$	Yes	88	14.4	12	267/36	124/75	13	L	Excellent detergent and dispersant	Dispersions, high temperature systems
TRITON™ X-165 (50%)	\$	Yes	>100	15.5	16	not run/40	115/45	2	L	Excellent emulsion stabilizer and dispersant	Paints and coatings, dispersions
TRITON™ X-165 (70%)	\$	Yes	>100	15.5	16	570/39	124/68	22	L	Excellent emulsion stabilizer and dispersant	Paints and coatings, dispersions
TRITON™ X-305 (70%)	\$	Yes	>100	17.3	30	1916/49	103/25	-7	L	Excellent emulsion stabilizer, provides freeze thaw and ionic stability	Emulsion polymerization, paints and coatings, floor polish, wax emulsions
TRITON™ X-405 (70%)	\$	Yes	>100	17.6	35	2442/52	93/22	-6	L	Excellent emulsion stabilizer, provides freeze thaw and ionic stability	Emulsion polymerization, paints and coatings floor polish, and wax emulsions
TRITON™ X-705 (70%)	9	Yes	>100	18.4	55	3585/44	80/55	2	L	Excellent emulsion stabilizer	Emulsion polymerization

Readily biodegradable

CleanGredients™

EPA inerts list

EU Ecolabel

Footnotes:

¹APE = Alkyl phenol ethoxylate ²Cloud point: °C, 1 wt% actives aqueous solution

³HLB range: <10 w/o emulsifier, >10 o/w emulsifier, 10-15 good wetting, 12-15 detergents ⁴Critical micelle concentration: ppm at 25°C

⁵Surface tension: dynes/cm at 1 ¹% actives, 25°C ⁶Ross-Miles foam height: mm at 0.1 wt% actives, 25°C, initial / 5 minute

⁷Pour point: °C ⁸Form at 25°C: L = Liquid, S = Solid MWF= Metalworking fluids Ins = Insoluble

Disp = Dispersible PRT = Proprietary

Bio-based nonionic surfactants

Product	Product highlights	APE based ¹	Cloud point ²	HLB ³	Moles EO	CMC ⁴ / surface tension ⁵	Foam height ⁶	Pour point ⁷	Form ⁸	Features	Applications
	A Series Nonion	ic Surfactar								stants based on seed oil based materials. These surfacta y are ideal candidates for paints & coatings, household a	
ECOSURF™ SA-4	9 \$	No	Disp	7.5	PRT	Disp	Disp	-8	L	Based on seed oil, low odor, no gel range, excellent wetting, oil soluble emulsifier	Concentrates, cleaners and detergents, prewash spotters, dry cleaning, paints and coatings, textile processing
ECOSURF™ SA-7	98	No	37	9.7	PRT	17/29	100/20	3	L	Based on seed oil, low odor, no gel range, rapid dissolution, excellent wetting and detergency, effective emulsifier	Concentrates, cleaners and detergents, prewash spotters, paints and coatings, textile processing, agrochemicals
ECOSURF™ SA-9	9 \$ Control	No	57	11.1	PRT	22/29	100/20	4	L	Based on seed oil, low odor, no gel range, rapid dissolution, excellent wetting and detergency, effective emulsifier	Concentrates, cleaners and detergents, prewash spotters, paints and coatings, textile processing
ECOSURF™ SA-15	9 \$	No	>100	13.5	PRT	153/34	130/25	27	S	Based on seed oil, low odor, rapid dissolution, excellent wetting and detergency especially at higher temperatures, effective emulsifier	Concentrates, cleaners and detergents, prewash spotters, paints and coatings, textile processing, agrochemicals
	CO Series are bi	odegradabl	le nonionic s							erent degrees of ethoxylation. These surfactants offer po polymer architecture according to customer requests and	
TERGITOL™ ECO-20	98	No	Disp	10	20	56/40	50/25	-30	L	Excellent emulsifier and dispersant, water dispersable	Agrochemicals, textile and leather processing, household and institutional cleaning
TERGITOL™ ECO-30 HP	98	No	>100	-	30	53/41	68/60	0	L	Excellent emulsifier and dispersant, water soluble. High purity grade, low salts concentration	Agrochemicals, textile and leather processing, household and institutional cleaning
TERGITOL™ ECO-36	98	No	80	13	36	44/40	60/50	12	L	Excellent emulsion stabilizer	Agrochemicals, textile and leather processing, household and institutional cleaning
TERGITOL™ ECO-40	9 \$	No	80	13	40	50/40	60/55	15	L	Excellent emulsion stabilizer	Agrochemicals, textile and leather processing, household and institutional cleaning

Readily biodegradable

€ CleanGredients™

€ EPA inerts list

EU Ecolabel







Footnotes:
¹APE = Alkyl phenol ethoxylate
²Cloud point: °C, 1 wt% actives aqueous solution

³HLB range: <10 w/o emulsifier, >10 o/w emulsifier, 10-15 good wetting, 12-15 detergents

⁴Critical micelle concentration: ppm at 25°C

*Surface tension: dynes/cm at 1% actives, 25°C

*Ross-Miles foam height: mm at 0.1 wt% actives, 25°C, initial / 5 minute

⁷Pour point: °C

⁸Form at 25°C: L = Liquid, S = Solid MWF= Metalworking fluids


ECOSURF™ products are sold under trade name TERGITOL™ in Canada and Japan.

Ins = Insoluble Disp = Dispersible PRT = Proprietary

10

Bio-based nonionic surfactants

Product	Product highlights	APE based¹	Cloud point ²	HLB ³	Moles EO	CMC ⁴ / surface tension ⁵	Foam height ⁶	Pour point ⁷	Form ⁸	Features	Applications
TRITON™ Alkyl Po TRITON™ BG and TF concentrations are no	RITON™ CG Spe	cialty Surfac	tants are no	n-ionic pro	oducts use	ed in househ	old and indu	ıstrial and i	nstitutional	l detergent formulations where high, stable foam is require	ed or where high caustic
TRITON™ BG-10	263	No	>100	-	0	1591/28	112/115	-5	L	Soluble in highly alkaline solutions, good detergency and wetting properties, mild, listed on CleanGredients™ and US EPA Safer Choice Formulations	Bottle washing, metal cleaners, highly alkaline detergents, paint strippers, aluminum brighteners, agrochemicals
TRITON™ CG-50	9 & 3	No	>100	-	0	870/27	112/112	0	L	Soluble in highly alkaline solutions, mild, good detergent and wetter, high stable foam, listed on CleanGredients™ for US EPA Safer Choice Formulations	Bottle washing, metal cleaners, highly alkaline detergents, paint strippers, aluminum brighteners, agrochemicals
TRITON™ CG-110	263	No	>100	-	0	1748/27	105/100	-15	L	Soluble in highly alkaline solutions, mild, low skin drying effects, good detergent and wetter, high stable foam, listed on CleanGredients™ and US EPA Safer Choice Formulations	Bottle washing, metal cleaners, highly alkaline detergents, paint strippers, aluminum brighteners, agrochemicals
TRITON™ CG-425	263	No	>100	-	0	61/29	140/140	-18	L	Soluble in highly alkaline solutions, mild, good detergent and wetter, high stable foam	Glass cleaners, highly alkaline detergents
TRITON™ CG-600	263	No	>100	-	0	74/29	80/80	6	L	Soluble in highly alkaline solutions, mild, good detergent and wetter, high stable foam	Glass cleaners, highly alkaline detergents
TRITON™ CG-650	263	No	>100	-	0	67/29	110/110	-18	L	Soluble in highly alkaline solutions, mild, good detergent and wetter, high stable foam	Glass cleaners, highly alkaline detergents











Footnotes:

'APE = Alkyl phenol ethoxylate

'Cloud point: °C, 1 wt% actives aqueous solution

'HLB range: <10 w/o emulsifier, >10 o/w emulsifier, 10-15 good wetting, 12-15 detergents

'Critical micelle concentration: ppm at 25°C

'Surface tension: dynes/cm at 1% actives, 25°C

'Poss Miles from beight mm at 0.1 wt% actives 25°C

'Poss Miles from beight mm at 0.1 wt% actives 25°C

'Poss Miles from beight mm at 0.1 wt% actives 25°C

⁶Ross-Miles foam height: mm at 0.1 wt% actives, 25°C, initial / 5 minute

⁷Pour point: °C °Form at 25°C: L = Liquid, S = Solid MWF= Metalworking fluids Ins = Insoluble


Disp = Dispersible PRT = Proprietary

Polypropylene glycols and random copolymers

Product	Product highlights	APE based¹	Molecular weight	Specific gravity² @25/25°C	Average viscosity³, cSt @40°C	Pour point, °C	Refractive index⁴ @25°C	Density lb/gal @25°C	Features	Applications
	e Glycols are pol								nd water solubility decreases with increasing molecularyl ether polymers containing three terminal hydroxyl g	
PT250	\$	No	250	1.091	285	-18	1.459	9.07	Compatibility, solvency, low toxicity, low odor, natural lubricity, low ash, non-varnishing, chemically stable	Synthetic lubricants, foam control, chemical intermediates, viscosity modifiers
PT700	\$	No	700	1.033	108	-32	1.453	8.59	Compatibility, solvency, low toxicity, low odor, natural lubricity, low ash, non-varnishing, chemically stable	Synthetic lubricants, foam control, chemical intermediates, viscosity modifiers
PT3000	\$	No	3000	1.01	235	-27	1.451	8.40	Compatibility, solvency, low toxicity, low odor, natural lubricity, low ash, non-varnishing, chemically stable	Synthetic lubricants, foam control, chemical intermediates, viscosity modifiers
PT4800	\$	No	4800	1.018	415	-25	1.45	8.5	Compatibility, solvency, low toxicity, low odor, natural lubricity, low ash, non-varnishing, chemically stable	Synthetic lubricants, foam control, chemical intermediates, viscosity modifiers
P425	9 \$	No	425	1.007	33	-45	1.447	8.39	Compatibility, solvency, low toxicity, low odor, natural lubricity, low ash, non-varnishing, chemically stable	Synthetic lubricants, foam control, chemical intermediates, cosolvents
P600	98	No	600	1.006	55	-25	1.447	8.39	Compatibility, solvency, low toxicity, low odor, natural lubricity, low ash, non-varnishing, chemically stable	Synthetic lubricants, foam control, chemical intermediates, cosolvents
P1000TB	98	No	1000	1.005	78	-25	1.448	8.38	Compatibility, solvency, low toxicity, low odor, natural lubricity, low ash, non-varnishing, chemically stable	Synthetic lubricants, foam control, chemical intermediates, cosolvents
P1200	98	No	1200	1.003	91	-40	1.448	8.38	Compatibility, solvency, low toxicity, low odor, natural lubricity, low ash, non-varnishing, chemically stable	Synthetic lubricants, foam control, chemical intermediates, cosolvents
P2000	9 \$	No	2000	1.002	160	-30	1.449	8.34	Compatibility, solvency, low toxicity, low odor, natural lubricity, low ash, non-varnishing, chemically stable	Synthetic lubricants, foam control, chemical intermediates, cosolvents
23000	98	No	3000	1.002	265	-25	1.45	8.36	Compatibility, solvency, low toxicity, low odor, natural lubricity, low ash, non-varnishing, chemically stable	Synthetic lubricants, foam control, chemical intermediates, cosolvents
P4000	98	No	4000	1.004	455	-26	1.45	8.36	Compatibility, solvency, low toxicity, low odor, natural lubricity, low ash, non-varnishing, chemically stable	Synthetic lubricants, foam control, chemical intermediates, cosolvents
Random Cop Polyglycol Co		lymers of eth	ylene oxide and	d propylene oxid	de. Polyglycol 15	-200 finds	utility where a v	vater soluble l	iquid with a low pour point is desired.	
5-200	\$	No	2400	1.069	180	51	1.460	8.90	Compatibility, solvency, low toxicity, low odor, natural lubricity, low ash, non-varnishing, chemically stable	Foam control, chemical intermediates, viscosity modifiers
Readily biod	degradable 🎳 Cle	anGredients™	EPA inerts list	t EU Ecolabe	l					

Footnotes: ¹APE = Alkyl phenol ethoxylate ²ASTM D 892 ³ASTM D 445/446 ⁴ASTM D 1218

	Product	APE	l I			Surface	tension ³	Fo	am⁴		
Product	highlights	based ¹	Actives	Diluent	Form ²	Neutral ⁵	Alkaline ⁶	Neutral⁵	Alkaline ⁶	Features	Applications
DOWFAX™ Alkyldi DOWFAX™ Surfacta and thermal degrada	ints are an excel			ons containii	ng acids, bl	each, or caus	tic. They prov	ide excellent	solubility and s	stability in concentrated electrolytes, and they're remarka	bly resistant to oxidative
DOWFAX™ 2A1 Surfactant	\$	No	45	Water	L amber	34	35	140/130	145/145	Excellent solubility and stability in acidic, alkaline, bleach and other oxidizing systems, dispersant, emulsion stabilizer, rinses easily from surfaces	Cleaners, textile, pulp/paper, agrochemica oilfield, emulsion polymerization, fragrance solubilization
DOWFAX™ 3B2 Surfactant	\$	No	45	Water	L yellow/ It brown	37	38	135/135	140/120	Excellent stability in alkaline, acid, bleach and oxidizing systems, hard water tolerant, rinses easily from surfaces	Textile and pulp/paper processing, agrochemicals, oilfield, cleaners
DOWFAX™ 8390 Surfactant	\$	No	35	Water	L light brown	44	46	120/25	140/25	Emulsion stabilizer, excellent solubility, stable in oxidizing systems, high level of particulate soil detergency, excellent rinseability	Emulsion polymerization, cleaners and detergents, oil field chemicals, textile, pulp and paper
DOWFAX™ C6L Surfactant	-	No	45	Water	L light brown	34	34	145/140	145/130	Reduces gelation, provides coupling, excellent solubility and stability, hypochlorite stable, low visible residue, rinses easily from surfaces, hydrotrope	Cleaners and detergents, oilfield chemicals
DOWFAX™ C10L Surfactant	8	No	45	Water	L yellow/ brown	35	37	135/125	130/115	Low streaking and low visible residue, rapid dissolution, excellent stability	Glass and all-purpose cleaners and other detergents, agrochemicals
TRITON™ GR Dioc TRITON™ GR Series paint and coatings,	s surfactants fea	ture excelle			properties a	as well as exc	ellent emulsify	ring and dispe	ersing ability. T	These versatile surfactants are available in a range of solv	
TRITON™ GR-5M	98	No	60	IPA ⁷ / water	L colorless	26	NR ⁸	190/180	NR	Excellent wetting, emulsifying and dispersing ability	Paints and coatings, paper and textile, agrochemicals, cleaners, oilfield
TRITON™ GR-7M	9 3	No	64	Petroleum distillate ⁹	L amber	Ins	Ins	Ins	Ins	Excellent emulsifying and dispersing ability, oil soluble	Dry cleaning, paints and coatings, agrochemicals, oilfield chemicals
TRITON™ Phospha TRITON™ H-55, TR emulsification polym	TON H-66, and	TRITON QS	6-44 are anio	nic hydrotrop	oes that pro	vide solubiliza	ation for nonio	nic surfactan	ts in low to hig	yhly built cleaner systems. TRITON QS-44 and TRITON X	QS-20 surfactants are also used in
TRITON™ H-55	9	No	50	Water	L amber	45	53	8/0	25/0	Hydrotrope, stable in acidic and alkaline conditions	Solubilizer for surfactants into highly built detergents
TRITON™ H-66	9	No	50	Water	L yellow	45	41	50/8	105/25	Hydrotrope, stable in acidic and alkaline conditions, uniquely effective with low foam surfactants	Solubilizer for surfactants into built detergents and other formulated systems
TRITON™ QS-44	-	Yes	80	Water	L amber	38	39	130/65	150/140	Hydrotrope with surface activity, good solubility in alkali, stable on solid caustic, hypochlorite stable	Cleaners, emulsion polymerization, agrochemicals, solubilizer for low built detergents
TRITON™ XQS-20	-	Yes	70	Water	L amber	46	46	145/130	130/120	High HLB emulsifier and stabilizer	Emulsion polymerization
TRITON™ Sulfates TRITON™ sulfate ar	d sulfonate anio	nic surfacta	ants offer exc	cellent wettin	g, emulsifyii	ng, dispersing	g and stabilizir	ng ability. App	olications inclu	de emulsion polymerization, wax emulsification, textile pr	ocessing, and cleaners.
TRITON™ QS-15	-	No	100	None	L amber	33	36	95/70	150/15	Excellent detergent, soluble and stable in hot alkaline solutions, uniquely effective in high soil loads	Highly alkaline metal cleaners, bottle washing, zinc plating brightener, gas well cleaning
TRITON™ XN-45S	-	Yes	60	Ethanol/ water	L amber	33	32	170/165	170/170	Excellent wetting, emulsifying and dispersing ability, hypochlorite stable	Emulsion polymerization, wax emulsification, cleaners



Footnotes:

'APE = Alkyl phenol ethoxylate

'Form at 25°C: L = Liquid, S = Solid

'Surface Tension: dynes/cm at 1 wt% actives, 25°C

'Ross-Miles foam height: mm at 1 wt% actives, 25°C, initial / 5 minute

'Actual pH = 7 (distilled water)

⁶Actual pH = 12.5 (sodium hydroxide solution) ⁷IPA = Isopropanol

**NR = Not recommended; can hydrolyze under some alkaline conditions

Blend of ethanol, naphtha, propylene glycol and naphthalene

Ins = Insoluble

Low foam surfactants

	ECOSURF™ LFE-635	ECOSURF™ LFE-1410	TRITON™ DF-12	TRITON™ DF-16	TRITON™ DF-20
Product highlights	268	268	S Covided	2 S Corder	2
Dow low foam surfactants include specialty products used in applications where low- to n as well as caustic and acid stability.	o-foam performance is required. Th	nese high performance solution	ons provide excellent deterger	ncy and wetting properties,	
Typical physical properties					
Active ingredient, wt %	100	100	100	100	100
Cloud point, 1% aqueous soln, °C (°F)	35	10	17 (63)	36 (97)	_
HLB (calculated)	10.5	8.4	10.6	11.6	_
Surface tension ¹	32	35	34	30	30
Critical Micelle Concentration (CMC), ppm	315	85	290	530	180
- Viscosity at 25 °C (77 °F), cP			60	35	630
- Pour point, ASTM D 97, °C (°F)	-42	5	16 (61)	-6 (22)	-25 (-13)
APE-based	No	No	No	No	No
Performance characteristics					
Stability on solid caustic	Poor	Poor	Good	Poor	NR ²
Stability in nonoxidizing acids	Excellent	Excellent	Good	Excellent	NR
Chlorine stability in dry-blended powders⁴	NR	NR	NR	NR	NR
Food soil defoaming	Good	Good	Good	Poor	_
Soap soil defoaming	Poor	Poor	Fair	Poor	_
Foaming performance minimum water temperature for low foam, °C (°F)	38 (100)	16 (60)	16 (60)	38 (100)	43 (110)
Applications					
Food and dairy cleaners	•	•	•	•	
lon exchange resin cleaners	•			•	
Machine dishwash	•	•	•		
Metal cleaners	•	•	•	•	•
Pigment dispersions	•			•	
Pulp and paper	•	•	•	•	
Rinse aids	•	•	•	•	
Textile processing	•			•	
Wetting agent	•	•	•	•	



Readily biodegradable CleanGredients EPA inerts list EU Ecolabel





ECOSURF™ products are sold under trade name TERGITOL™ in Canada and Japan.

Footnotes:
¹1 wt% actives, dynes/cm
²NR - Not Recommended
³Excellent stability; however, moderate foaming in acid systems. Use in combination with TRITON™
CF-10 or another low foam surfactant for improved low foaming performance in acid systems.

⁴With organic chlorine release agent

Low foam surfactants

	TERGITOL™ MinFoam 2X	TERGITOL™ MinFoam 1X	TRITON™ CF-10/CF-10 (90%)	TRITON™ CF-21	TRITON™ CF-32	TRITON™ CF-76	TRITON™ CF-87
Product highlights	\$	\$	-	-	-	-	-
Dow low foam surfactants include specialty products used in applications where low- to no-foam performance is required. These high performance solutions provide excellent detergency and wetting properties, as well as caustic and acid stability.							
Typical physical properties							
Active ingredient, wt %	100	100	100	100	95	100	90
Cloud point, 1% aqueous soln, °C (°F)	21	40	28 (82)	40 (104)	25 (77)	31 (88)	32 (90)
HLB (calculated)	12.1	12.6	12.6	12.9	11	12.6	12.7
Surface Tension ¹	31	30	36	32	37	33	34
Critical Micelle Concentration (CMC), ppm	24	34	75	130		25	80
- Viscosity at 25 °C (77 °F), cP	56	61	250	250	550	295	240
- Pour point, ASTM D 97, °C (°F)	<-40 (<-40)	-34 (-20)	15 (59) / -1 (30)	-27 (-16)	2 (35)	7 (45)	0 (32)
APE-based	No	No	Yes	Yes	No	Yes	Yes
Performance characteristics							
Stability on solid caustic	Poor	Poor	Fair	Poor	Poor	Excellent	Good
Stability in nonoxidizing acids	Excellent	Excellent	Good	Excellent	Excellent ³	NR	Good
Chlorine stability in dry-blended powders4	NR	NR	Good	NR	Fair	Good	NR
Food soil defoaming	Poor	Poor	Fair	Poor	Excellent	Good	Fair
Soap soil defoaming	Fair	Fair	Fair	Poor	Good	Good	Poor
Foaming performance minimum water temperature for low foam, °C (°F)	27 (80)	43 (110)	38 (100)	43 (110)	29 (85)	35 (95)	38 (100)
Applications							
Food and dairy cleaners					•	•	
Ion exchange resin cleaners				•			
Machine dishwash			•		•		
Metal cleaners	•	•	•	•		•	
Pigment dispersions	•	•	•	•			
Pulp and paper	•	•	•	•			
Rinse aids			•	•	•		•
Textile processing		•	•	•			
Wetting agent	•	•	•	•			•





Footnotes: 11 wt% actives, dynes/cm 2NR - Not Recommended

³Excellent stability; however, moderate foaming in acid systems. Use in combination with TRITON™ CF-10 or another low foam surfactant for improved low foaming performance in acid systems.
⁴With organic chlorine release agent

US, Canada, Mexico
Call 800 447 4369

Latin America

Call + 55 11 5184 8722

Europe

Call toll-free + 800 3 694 6367* Call + 31 11567 2626 Asia / Pacific
Call toll-free

Call toll-free + 800 7776 7776* Call + 60 3 7965 5392

*Toll free service not available in all countries

www.dowsurfactants.com

 $Images: Cover - dow_57804035694; page\ 2 - dow_57715656668, dow_57234119449; page\ 3 - dow_55277734546; page\ 4 - dow_53989421204, dow_56386671556668, dow_5638667155668, dow_5638667156668, dow_5638667156668, dow_5638667156668, dow_56386668, dow_56386668, dow_563866668, dow_563866668, dow_563866668, dow_563866666, dow_56386666, dow_5638666, dow_56386666, dow_5638666, dow_5638666, dow_56386666, dow_5638666, dow_5638666, dow_56386666, dow_5638666, dow_56386666, dow_5638666, dow_5638666, dow_56386666, dow_5638666, dow_56386666, dow_56386666, dow_56386666, dow_563866666, dow_56386666, dow_56386666, dow_56386666, dow_56386666, dow_56386666, dow_563866$

Notice: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, the Customer is responsible for determining whether products and the information in this document are appropriate for the Customer's use and for ensuring that the Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Dow assumes no obligation or liability for the information in this document. No warranties are given; all implied warranties of merchantability or fitness for a particular purpose are expressly excluded. This document is intended for global use.

®TM Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow unless otherwise specified

© 2024 The Dow Chemical Company. All rights reserved.

2000024567-7647 Form No. 119-01491-01-0524 S2D