



MyTrends

Engage & Embrace

We celebrate diversity and individuality while being responsible and fully engaged. Today's motto: contribute to society in a positive way, embrace our well-being and the environment and shape a society with positive values. Our credo: DO.

Infinite Glance

Universal Mascara
CPF 4130

Attributes

- 2-in-1 for lash/brow
- Thicken/separate lashes
- Natural look
- Water resistant
- Long-lasting top coat
- Non-transfer top coat

Featured Products

- DOWSIL™ MQ-1600 Solid Resin
- XIAMETER™ PMX-200 Silicone Fluid 2CS
- DOWSIL™ FC-5002 IDD Resin Gum
- DOWSIL™ EL-7040 Hydro Elastomer Blend
- DOWSIL™ BY 25-337 Emulsifier
- DOWSIL™ 3901 Liquid Satin Blend
- DOWSIL™ VM-2270 Aerogel Fine Particles

Visit consumer.dow.com/personalcare and dow.com/en-us/industries/consumer/personal-care (organic solutions) to see Dow at work and learn more about the technologies that make consumer products better.

DOW DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

©™ Trademark of The Dow Chemical Company (Dow) or an affiliated company of Dow

© 2019 The Dow Chemical Company. All rights reserved.

Phase	Trade Name / Supplier	INCI Name	Wt. %
A	DOWSIL™ MQ-1600 Solid Resin / Dow	Trimethylsiloxysilicate	6.70
	XIAMETER™ PMX-200 Silicone Fluid 2CS / Dow	Dimethicone	13.30
	DOWSIL™ FC-5002 IDD Resin Gum / Dow	Isododecane (and) Trimethylsiloxysilicate / Dimethiconol Crosspolymer	20.00
B	DOWSIL™ EL-7040 Hydro Elastomer Blend / Dow	Caprylyl Methicone (and) PEG-12 Dimethicone / PPG-20 Crosspolymer	12.80
	DOWSIL™ BY 25-337 Emulsifier / Dow	PEG / PPG-19 / 19 Dimethicone (and) C13-16 Isoparaffin (and) C10-13 Isoparaffin	5.00
	DOWSIL™ 3901 Liquid Satin Blend / Dow	Dimethicone (and) Dimethicone / Vinyl Dimethicone Crosspolymer	5.00
	DOWSIL™ VM-2270 Aerogel Fine Particles / Dow	Silica Silylate	0.30
		Water / Aqua	17.50
C		Glycerin	8.50
	Propylene Glycol / Dow	Propylene Glycol	10.00
	NEOLONE™ PH 100 Preservative / DuPont	Phenoxyethanol	0.90

Procedure

1. Using phase A ingredients, disperse the resin into the fluid until it is a uniform clear liquid.
2. One at a time in the order listed, add phase B ingredients to phase A and mix until uniform.
3. Separately, combine and mix phase C ingredients until uniform.
4. Slowly add phase C to phase AB under mixing at 700 rpm. After the addition is complete, mix at 2000 rpm.
5. Pass through a high-shear mixer (ex: Silverson).

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

TO THE FULLEST EXTENT PERMITTED BY APPLICABLE LAW, DOW SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. 27-2310-01



consumer.dow.com